



1 SECOND LEVEL FLOOR PLAN
SCALE: 1/4" = 1'-0"

GENERAL PARTITION LEGEND	
<p>2x4 WOOD STUD @ 16" O.C. W/ (1) SPLY. 1/2" GYP. BR. ON EXTERIOR SIDE ONLY</p>	<p>2x8 WOOD STUDS @ 16" O.C. USE 7" GYP. BR. ON EXTERIOR SIDE ONLY</p>
<p>2x4 WOOD STUD @ 16" O.C. W/ (1) SPLY. 1/2" GYP. BR. ON ALL INTERIOR FACES</p>	<p>2x4 WOOD STUD @ 16" O.C. W/ (1) SPLY. 1/2" GYP. BR. ON ALL INTERIOR FACES</p>
<p>2x4 WOOD STUD @ 16" O.C. W/ (1) SPLY. 1/2" GYP. BR. ON ALL INTERIOR FACES</p>	<p>2x4 WOOD STUD @ 16" O.C. W/ (1) SPLY. 1/2" GYP. BR. ON ALL INTERIOR FACES</p>

- GENERAL PARTITION NOTES**
- ALL DIMENSIONS ARE TO FACE OF CORE FINISH UNLESS NOTED OTHERWISE. "CLEAN" DENOTES FACE OF FINISH.
 - RIN GYPSUM BOARD (GWB) FINISH ON ALL UNGRADED AREAS. FINISH SHALL BE RESPONSIBLE TO PROVIDE SMOOTH SURFACE TO WHICH FINISH SHALL BE APPLIED.
 - ALL CORNER JOINTS AND JOINTS OF GYPSUM BOARD SHALL BE REINFORCED WITH MESH TAPE TO COMPLETE C.M.E. INSTALLATION. (1" MIN. SETBACK)
 - ALONG PERIMETER WALLS AND CEILING WALLS RUN ALL PENETRATIONS THROUGH THESE WALLS MUST BE SEALED AND FIRESTOPPED.
 - USE RESISTANT GYPSUM BOARD AT ALL LOCATIONS WHERE PENETRATIONS ARE REQUIRED. PENETRATIONS HAVE BEEN INDICATED. C.C. SHOULD REFER TO FINISH SCHEDULES FOR LOCATIONS AND ADDITIONAL REQUIREMENTS.
 - PROVIDE WATERPROOF MEMBRANE ON EXISTING SLAB IN AREAS TO RECEIVE THE FLOORING. TURN MEMBRANE UP AT LEAST 6" @ WALL IN KITCHEN, BAR AREA, AND BATHROOM TO RECEIVE FLOORING. VERIFY WITH SUB CONTRACTOR BEFORE WORK IS STARTED.
 - PREPARE BASE WALL MATERIALS (GYPSUM BOARD, SHEETROCK, etc.) TO RECEIVE FINISHES INDICATED. FINISHES SHALL BE RESPONSIBLE TO PROVIDE SMOOTH SURFACE TO WHICH FINISH SHALL BE APPLIED.
 - ALL WALL SURFACES IN KITCHEN AND FOOD PREP AREAS, TO COMPLETE C.M.E. INSTALLATION, SHALL BE FINISHED WITH ALL PENETRATIONS THROUGH THESE WALLS MUST BE SEALED AND FIRESTOPPED.

- CONSTRUCTION NOTES**
- CUT OPENING IN EXISTING EXTERIOR WALL TO CREATE EXISTING GRADE. INSTALL W/ WOOD FRAMING TO MATCH EXISTING FLOOR CONSTRUCTION. FINISH PERMITS.
 - EXPAND EXISTING OPENING. INSTALL NEW STEEL UNITS. EXISTING CLASS W/ NEW 1" INSULATED CLASS WALLS.
 - INSTALL NEW ALUMINUM DIMMERS @ EXISTING COLUMNS.
 - EXPAND EXISTING OPENING. INSTALL NEW STEEL UNITS. EXISTING CLASS W/ NEW 1" INSULATED CLASS WALLS. DOOR TO EXTERIOR.
 - INSTALL NEW WAMP. READY TO BE CONSTRUCTED USING WOOD FRAMING W/ 7" RYWOOD SHEATHING @ FACE TO BE 1/2" MAX.
 - CUT OPENING IN EXISTING WALL TO CREATE NEW WINDOWS. INSTALL NEW UNITS AS REQUIRED.
 - INSTALL NEW CONTINUOUS WOOD SHELF FRAMED BOARD W/ 7" DIAMETER STAINLESS STEEL CLOTHING ROD.
 - EXISTING DOORS TO REMAIN. DOORS SHALL BE FINISHED IN AREAS TO RECEIVE THE FLOORING. TURN MEMBRANE UP AT LEAST 6" @ WALL IN KITCHEN, BAR AREA, AND BATHROOM TO RECEIVE FLOORING. VERIFY WITH SUB CONTRACTOR BEFORE WORK IS STARTED.
 - PREPARE BASE WALL MATERIALS (GYPSUM BOARD, SHEETROCK, etc.) TO RECEIVE FINISHES INDICATED. FINISHES SHALL BE RESPONSIBLE TO PROVIDE SMOOTH SURFACE TO WHICH FINISH SHALL BE APPLIED.
 - ALL WALL SURFACES IN KITCHEN AND FOOD PREP AREAS, TO COMPLETE C.M.E. INSTALLATION, SHALL BE FINISHED WITH ALL PENETRATIONS THROUGH THESE WALLS MUST BE SEALED AND FIRESTOPPED.
 - EXPAND EXISTING OPENING. INSTALL NEW STEEL UNITS. EXISTING CLASS W/ NEW 1" INSULATED CLASS WALLS. DOOR TO EXTERIOR.
 - INSTALL NEW WAMP. READY TO BE CONSTRUCTED USING WOOD FRAMING W/ 7" RYWOOD SHEATHING @ FACE TO BE 1/2" MAX.
 - CUT OPENING IN EXISTING WALL TO CREATE NEW WINDOWS. INSTALL NEW UNITS AS REQUIRED.
 - INSTALL NEW CONTINUOUS WOOD SHELF FRAMED BOARD W/ 7" DIAMETER STAINLESS STEEL CLOTHING ROD.

ROLLER
ARCHITECTS - LLC
1128 Walnut Street, Suite 300
P.O. Box 8191
SALEM, NJ 08073
TEL: 201.528.3931 FAX: 201.528.3118

SALEM CITY

113-119 MARKET STREET
SALEM, NJ 08073

Second Floor Plan

DATE: 06.01.2008
DRAWN BY: MJK/DVB/HWH
FILE: A12.dwg
REVISIONS: Klg/mwd

0 4' 8'

A1.2
PERMIT SET